Product Name: Duracourt, Blue

Product Code: 170 Date issued: 12/14/2022

SECTION 1: IDENTIFICATION

Product Name Duracourt, Blue

Product Code # 170

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings

1445 South 15th Street P.O. Box 3726

Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity - Oral 4 & 5

Skin Irritant 2

Eye Damage/Irritation 2b

GHS Label Elements

Hazard Symbols



Signal Word Warning

Hazard Statements

H302 Harmful if swallowed H315 Causes skin irritation H320 Causes eye irritation

Precautionary statements

Prevention

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands and/or face thoroughly after handling.

Response

P330 If swallowed, rinse mouth.

P363 Wash contaminated clothing before reuse.

P301 + P310 If swallowed: Immediately call a poison center or doctor. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage/ Disposal

P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Product Name: Duracourt, Blue

Product Code: 170 Date issued: 12/14/2022

SECTION	3 : COMPOSITION INFORMATION	N

Chemical Designation	CAS No.	% by Weight
nepheline syenite	37244-96-5	20 - 30%
ground limestone	1317-65-3	20 - 30%
titanium dioxide	13463-67-7	1 - 5%
ethylene glycol	107-21-1	1 - 5%
butoxy dipropanol	29911-28-2	1 - 5%
crystalline silica, (quartz)	14808-60-7	0.1 - 1%

SECTION 4: FIRST AID MEASURES

Show this safety data sheet to the doctor in attendance General Advice

Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate Eyes:

medical attention.

Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention. Skin:

Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention. Inhalation:

Do not induce vomiting – seek immediate medical attention. Ingestion:

Notes to Physician Treat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Extinguishing Media:

Specific Hazards arising Closed containers may rupture if exposed to fire or extreme heat.

from the Chemical

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective Special protective

Equipment:

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment. Remove all sources of ignition.

Environmental Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from Precautions

entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

Methods for Clean-up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly. Other Information None known

SECTION 7: HANDLING & STORAGE

Handling: Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children. Storage:

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*11

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD,

* - Chronic Hazard

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

Exposure Limits

(R) = Respirable fraction

OSHA PEL ACGIH TLV **Hazardous Components** nepheline syenite 5 ppm (R) NE. ground limestone 15 mg/m3 (R) NE titanium dioxide 15 mg/m3 10 mg/m3 ethylene glycol 50 ppm (C)(STEL) 50 ppm (C) butoxy dipropanol NE. crystalline silica, (quartz) $10 \text{ mg/m} \frac{3}{\%} \text{Sio} 2 + 2 (R)$ 0.025 mg/m3 (R)

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Product Name: Duracourt, Blue

Product Code: 170 Date issued: 12/14/2022

Personal Protective Equipment

Eyes/Face: Safety goggles or full face shield **Skin:** Protective gloves and impervious clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Hygiene Practices: Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: liquid

Odor: Little or no odor Odor threshold: Not determined

 VOC lb/gal
 0.44
 VOC (g/L)
 52.85

 VOC (lb/gal) less exempt
 0.79
 VOC (g/L) less exempt
 95.29

 Relative Density (LB/GAL):
 13.36
 Specific Gravity (g/L):
 1.60

Flash Point (F): Greater than 201

Flammability: Not applicable Upper/lower flammability limits: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Not determined

Evaporation rate: Not available

Not available Vapor Pressure (mmHg): Vapor Density: Not available Initial Boiling Point (F): 212 Boiling Point Range (F): Not available Freezing Point (F): 32 Melting Point (F): Not determined Not available Viscosity Not available pН

Solubility (ies): Not determined
Partition coefficient: n- Not determined

octanol/water

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Prevent from freezing

Materials to Avoid:
Hazardous Decomposition Products:
Possibility of Hazardous Reactions:

No materials to be especially mentioned.
None under normal use.
None under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
nepheline syenite	NA	NA	NA
ground limestone	NA	NA	NA
titanium dioxide	10,000	10,000	6.82
ethylene glycol	NA	NA	NA
butoxy dipropanol	NA	NA	NA
crystalline silica, (quartz)	500	NA	NA

Chronic Toxicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

ComponentIARCNTPOSHAtitanium dioxide2B – Possible Human CarcinogenNot listedListedcrystalline silica, (quartz)1 – Human carcinogenKnown Human CarcinogenListed

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints.

SECTION 12: ECOLOGICAL INFORMATION

No ecological information available

Product Name: Duracourt, Blue

Product Code: 170 Date issued: 12/14/2022

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary,

consult your sanitation department or state-designated environmental protection agency for more disposal

ontions

SECTION 14: TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA: Yes - All components are listed or exempt

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard YES Chronic Health Hazard YES Fire Hazard NO Sudden Release of Pressure NO

Hazard

Reactive Hazard NO

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation Cas No. Weight % 107-21-1 ethylene glycol < 5%

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS)

Chemical Designation Cas No. Weight % ethylene glycol 107-21-1 1.62

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 12/14/2022 VER 02

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.